



SHAPED FOR PERFORMANCE



SPECIFICATIONS		DATENBLATT	
Name	OXO OPTIMAL FRESH	Handelsname	OXO OPTIMAL FRESH
Material	Polyethylene	Material	Polyethylen
Additives	Stabilizers / Anti UV	Additive	UV-Stabilisator
Base/Bubble Colouring	Crystal/White	oben/Luftkammer Farbe	Durchscheinend/Weiß
Colouring code	5164	Farbcode	5164
Weight per m² (g/m²)	458 ± 8%	Gewicht pro m² (g/m²)	458 ± 8%
Thickness	500µ ± 8%	Dicke	500µ ± 8%
Diameter of O bubble	16 mm	Durchmesser der Luftkammer O	16 mm
Diagonal of X Bubble	26 mm	Durchmesser der Luftkammer X	26 mm
Bubble spacing	2.5 mm et 3.5 mm	Abstand der Luftkammer	2.5 mm et 3.5 mm
Height of bubbles	5 mm	Höhe der Luftkammer	5 mm
Vicat Softening Temperature	96,2°C	Vicat-Erweichungstemperatur	96,2°C
Brittle point : Cold crack temperature	-74,7°C	Kaltrisstemperatur	-74,7°C
Bubble surface area	72%	Blasenförmiger Bereich	72%
Volume of air per m²	380 cl	Luftvolumen pro 1 m²	380 cl
Roll Length	De 50 à 80 ml ± 1ml	Rollenlänge	De 50 à 80 ml ± 1ml
Welding Edges	De 0 à 40 mm	Schweisskante	De 0 à 40 mm
Roll Diameter	60 cm (Roll of 50ml)	Rollendurchmesser	60 cm (Roll of 50ml)
Core Diameter	Internal 76 mm	Kerndurchmesser	Internal 76 mm
Identification	Individual Label with article description	Kennzeichnung	Individual Label with designation Article
Warranty*	5 years	Garantie*	5 years

*Warranty based on laboratory aging tests and under normal conditions of use

*Garantie wird nach Alterungstests im Labor und unter normalen Nutzungsbedingungen gewährt



www.oxo-optimal.com

